



Thede & Witte
FERTIGPARKETT

Technical data sheet

T&W Boston 1-strip Oak matt lacquered/oiled/white washed/brushed/smoked/
hand-sawn

Dimensions

Length: 1860 mm
Width: 189 mm
Thickness: 15 mm

Product composition

Top layer: approx. 4 mm real wood
Core: 9 mm transverse poplar wood slats
Back veneer: 2 mm longitudinal poplar wood veneer



Slight bevel on long side, sharp edges on products with matt lacquered surfaces

Surface finish

Either 6-times UV hardened acrylic matt lacquered (suitable for residential areas) or naturally oxidative hardened oil surface – ready for interior use.
Suitable for residential and commercial areas with due regard to initial care and maintenance instructions recommended by the manufacturer.
For use on a natural oil surface in commercial areas, special measures are necessary after consultation with the manufacturer.

Glue

Preferre 4405 by dynea or equivalent

Connection

Uniclic® click system on long and short side

Country of origin

China

Packaging

8 boards per pack: 2.81 m²
40 packs per pallet: 112.40 m²

Certification

E1 classified; fire class Dfl-s 1.
Woca oil surface bears the IBR Seal of Approval for "recommended healthy living".
Suitable for warm water underfloor heating systems with due consideration of the standardized specifications. Suitable for professional floating installation or full-surface bonding.
Please observe and follow the installation (laying) instructions

As per: January 2017. Subject to change without prior notice