



**Thede & Witte**  
FERTIGPARKETT

# Technical data sheet

T&W Boston Finline - oiled

## Dimensions

Length: 2200 mm  
Width: 189 mm  
Thickness: 15 mm

## Product composition

Top layer: approx. 4 mm real wood  
Core: 9 mm transverse poplar wood slats  
Back veneer: 2 mm longitudinal poplar wood veneer



## Surface finish

Woca naturally oxidative hardened oil surface – ready for interior use.  
With due regard to initial care and maintenance instructions recommended by the manufacturers, suitable for residential and commercial areas.  
For use in commercial areas, special measures are necessary after consultation with the manufacturer.

## Glue

Prefere 4405 by dynea or equivalent

## Connection

Uniclic® click system on long and short side

## Country of origin

China

## Packaging

8 boards per pack: 3.33 m<sup>2</sup>  
40 packs per pallet: 133.20 m<sup>2</sup>

## Certification

E1 classified; fire class Dfl-s 1.  
Woca oil surface bears the IBR Seal of Approval for “recommended healthy living”.  
Suitable for warm water underfloor heating systems with due consideration of the standardized specifications. Suitable for professional floating installation or full-surface bonding.  
Please observe and follow the installation (laying) instructions.

As per: January 2017. Subject to change without prior notice