



Thede & Witte
FERTIGPARKETT

Technical data sheet

T&W Euro 1-strip – matt lacquered/oiled/thermally treated

Dimensions (deviations possible depending on the type of wood)

Length:	1800 mm	2200 mm	2000 mm/2200 mm
Width:	181 mm	181 mm	192 mm
Thickness:	15 mm	15 mm	15 mm

Product composition

Top layer: approx. 4 mm real wood,
Core: 8.5 mm transverse spruce wood slats
Back veneer: 2 mm longitudinal spruce wood veneer



Bevel on long side for oak, other wood sharp edge

Surface finish

Either 6-times UV hardened acrylic matt lacquered (suitable for residential areas) or naturally oxidative hardened oil surface – ready for interior use.

Suitable for residential and commercial areas with due regard to initial care and maintenance instructions recommended by the manufacturer.

For use on a natural oil surface in commercial areas, special measures are necessary after consultation with the manufacturer.

Glue

D3 Rakoll EBW 0301 (Fuller) or equivalent

Connection

Uniclic® click system on long side

Country of origin

EU

Packaging

8 boards per pack:	2.61 m ²	2.90 m ²	3.07 m ² / 3.19 m ²
40 packs per pallet:	104.40 m ²	116 m ²	122.80 m ² /127.60 m ²

Certification

E1 classified; fire class Dfl-s 1.

Suitable for warm water underfloor heating systems with due consideration of the standardized specifications. Suitable for professional floating installation or full-surface bonding.

Please observe and follow the installation (laying) instructions.

As per: January 2017. Subject to change without prior notice