



**Thede & Witte**  
FERTIGPARKETT

# Technical data sheet

T&W Europa 1-strip oiled

## Dimensions

Length: 1820 mm  
Width: 190 mm  
Thickness: 14 mm

## Product composition

Top layer: approx. 3.5 mm real wood  
Core: 8.5 mm transverse spruce wood slats  
Back veneer: 2 mm longitudinal spruce wood veneer



## Surface finish

Woca naturally oxidative hardened oil surface – with UV components, initial care of the new flooring is not necessary for residential areas. With due regard to initial care and maintenance instructions recommended by the manufacturers suitable for residential and commercial areas.

For use in commercial areas, special measures, depending on the type of area, are necessary after consultation with the manufacturer.

## Glue

D3 Rakoll EBW 0301 (Fuller) or equivalent

## Connection

Uniclic®/ Multifit

## Country of origin

EU

## Packaging

6 boards per pack: 2.08 m<sup>2</sup>  
66 packs per pallet: 104.30 m<sup>2</sup>

## Certification

E1 classified; fire class Dfl-s 1.

Suitable for warm water underfloor heating systems with due consideration of the standardized specifications. Suitable for professional floating installation or full-surface bonding.

Please observe and follow the installation (laying) instructions.

As per: January 2017. Subject to change without prior notice