



TECHNICAL DATA SHEET

BOSTON 1-STRIP OAK S

10 mm

DIMENSIONS

- **Length:** 1.860 mm
- **Width:** 148 mm
- **Thickness:** 10 mm

PRODUCT COMPOSITION

- **Top layer:** approx. 2.5 mm real wood
- **Core:** 5 mm plywood poplar
- **Back veneer:** 2 mm longitudinal poplar wood veneer

Slight bevel on long side, products with hand-planed surface on long and short side



SURFACE FINISH

WOCA naturally oxidative hardened oil surface – ready for interior use. With due regard to initial care and maintenance instructions recommended by the manufacturers, suitable for residential and commercial areas. For use in commercial areas, special measures are necessary after consultation with the manufacturer.

GLUE

Prefere 4405
by dynea or equivalent

CONNECTION

Uniclic® click system
on long and short side

COUNTRY OF ORIGIN

China

PACKAGING

- | | | |
|------------------|-----------|-----------------------|
| • Pack: | 12 boards | 3.30 m ² |
| • Pallet: | 42 packs | 138.60 m ² |

CERTIFICATION

E1 classified; fire class Dfl-s 1.

WOCA oil surface bears the IBR Seal of Approval for "recommended healthy living". Suitable for warm water (except Oak antique smoked white oiled) underfloor heating systems with due consideration of the standardized specifications. Suitable for professional floating installation or full surface bonding. Please observe and follow the installation (laying) instructions.