



# TECHNICAL DATA SHEET

## EURO 1-STRIP OAK

### DIMENSIONS

• <b>Length:</b>	2.200 mm	2.000 mm
• <b>Width:</b>	192 mm	192 mm
• <b>Thickness:</b>	15 mm	15 mm

### PRODUCT COMPOSITION

- **Top layer:** approx. 4 mm real wood
- **Core:** 9 mm transverse spruce wood slats
- **Back veneer:** 2 mm longitudinal spruce wood veneer

*Bevel on long side for oak, other wood sharp edge*



### SURFACE FINISH

Either 6-times UV hardened acrylic matt lacquered (suitable only for residential areas) or WOCA naturally oxidative hardened oil surface – ready for interior use. Suitable for residential and commercial areas with due regard to initial care and maintenance instructions recommended by the manufacturer. For use on a natural oil surface in commercial areas, special measures are necessary after consultation with the manufacturer.

### GLUE

D3 Rakoll EBW 0301 (Fuller)  
or equivalent

### CONNECTION

Uniclic® click system  
on long side

### COUNTRY OF ORIGIN

EU

### PACKAGING

• <b>Pack:</b>	8 boards	3,43 m <sup>2</sup>	3,07 m <sup>2</sup>
• <b>Pallet:</b>	40 packs	133,60 m <sup>2</sup>	122,80 m <sup>2</sup>

### CERTIFICATION

E1 classified; fire class Dfl-s 1.

Suitable for warm water underfloor heating systems with due consideration of the standardized specifications. Suitable for professional floating installation or full-surface bonding. Please observe and follow the installation (laying) instructions.